## UK Patent Application (19) GB (11) 2 389 130 (13) A

(43) Date of Printing by UK Office 03.12

•		(43) Date of Printing by UK Office	03.12.2003
(87) International Put WO2003/006778 (71) Applicant(s):	0305720.5 09.07.2002 (32) 09.07.2001 (33) US (32) 10.07.2001 (32) 20.09.2001 plication Data: 1520 En 09.07.2002 plication Data: En 23.01.2003	(51) INT CL <sup>7</sup> : E21B 7/12 21/08  (52) UK CL (Edition V ): E1F FBC FCC FGL  (56) Documents Cited by ISA: None  (58) Field of Search by ISA: Other: NOT YET ADVISED	
Baker Hughes Ind (Incorporated In 3900 Essex Lane, TX 77027, United	corporated USA - Texas) , Sulte 1200, Houston, I States of America		
	(continued on next page)		

- (54) Abstract Title: Drilling system and method for controlling equivalent circulating density during drilling of wellbores
- (57) A drilling system for drilling subsea wellbores includes a tubing-conveyed drill bit that passes through a subsea wellhead. Surface supplied drilling fluid flows through the tubing, discharges at the drill bit, returns to the wellhead through a wellbore annulus, and flows to the surface via a riser extending from the wellhead. A flow restriction device positioned in the riser restricts the flow of the returning fluid while an active fluid device controllably discharges fluid from a location below to just above the flow restriction device in the riser, thereby controlling bottomhole pressure and equivalent circulating density ("ECD"). Alternatively, the fluid is discharged into a separate return line thereby providing dual gradient drilling while controlling bottomhole pressure and ECD. A controller controls the energy and thus the speed of the pump in response to downhole measurement(s) to maintain the ECD at a predetermined value or within a predetermined range.

## GB 2389130 A continuation

- (72) Inventor(s):
  Peter Fontana
  Peter S Aronstam
  Larry Watkins
- (74) Agent and/or Address for Service: Murgitroyd & Company Scotland House, 165-169 Scotland Street, GLASGOW, G5 8PL, United Kingdom